



CPE SYSTEMS INC

ALL-PUR FDA F200

AODD PUMP



The All-Pur F200 AODD pump by All-Flo is specifically designed for the tough conditions of sanitary processing plants. The F200 can handle partial solids, a variety of temperatures, and is available in a range of materials to customize it to specific applications.

FEATURES


- Shear Sensitive
- Self-Priming
- Wide Temperature Range
- Simple Air Motor
- Streamline Bolted Design

DESIGN

The F-series pumps are designed for use in food processing and sanitary processing environments. With a simple bolted design and minimal moving parts, the F200 is durable, easy to repair and maintain, and incredibly reliable. All-Flo pumps are known for their performance and efficiency, with special features such as the high efficiency air valve that handles up to 120 psi of air pressure. All F-Series AODD pumps are operated with an air-compressor and do not require an electric motor.

OPERATION

The F200 has two diaphragms, a left and right which are connected with a rod. Pressurized air is used to move the diaphragms, alternating from left to right. When pressurized air moves the left diaphragm outwards, it in turn pulls the joined right diaphragm inwards. This causes the right side suction ball to move upward opening the inlet and the discharge ball to move down closing the outlet; this causes liquid to be suctioned into the chamber. When the pressurized air moves the diaphragm to the right the balls move opening the outlet and closing the inlet, this pushes the liquid out the discharge. This process occurs on both the left and right sides of the pump providing a more constant flow rate.



TECHNICAL SPECIFICATIONS

Physical Specifications

Air Inlet Connection Size:	3/4" FNPT
Air Exhaust Connection Size:	3/4"
Liquid Inlet:	2-1/2"
Liquid Discharge:	2-1/2"
Connection Type:	Tri-Clamp
Weight:	115 lbs (52 kg)

Porting:

Standard	Suction Right / Discharge Right
Special Order (Field Changeable)	Suction Right / Discharge Left
Special Order (Field Changeable)	Suction Left / Discharge Right
Special Order (Field Changeable)	Suction Left / Discharge Left

Materials

Wet End:	Passivated 316 Stainless Steel
----------	--------------------------------

Air End:

Standard	Aluminum
Special Order	Stainless Steel

Diaphragm:

TPE Model	Hytrel® (FDA)
PTFE Model	PTFE
Rubber Model	Santoprene® (FDA)

Valve/Ball:

Hytrel® Diaphragm	Buna-N (FDA)
PTFE Diaphragm	PTFE
Santoprene® Diaphragm	Santoprene® (FDA)

Seat:

Stainless Steel

O-Rings:

Hytrel® Diaphragm	Buna-N (FDA)
PTFE Diaphragm	PTFE
Santoprene® Diaphragm	EPDM (FDA)

Hardware:

Stainless Steel

Muffler:

Plastic
Metal (Special Order)

Operating Limits

Max Flow Rate:	190 gpm (719 lpm)
Max Pressure:	120 PSI (8.2 bar)
Max Solids Diameter:	1/4" (6.4 mm)
Max Suction Lift Capability (Dry):	24.4 ft-H ₂ O (7.4 m-H ₂ O)
Max Suction Lift Capability (Wet):	31.7 ft-H ₂ O (9.7 m-H ₂ O)

Approvals

FDA, CE, ATEX Compliant



F200 Common Models

The F200 has a variety of options to customize it to specific duties, including elastomer and air end materials, muffler options, porting options, and more. CPE Systems offer three base models that cover the majority of applications and needs. Other combinations and models are available upon request. Please contact the CPE Systems sales team for inquiries and special orders.

F200-TAE-TT3T-S70

- Connection Type: Tri-Clamp
- Air Section Material: Aluminum
- Diaphragm: PTFE
- Ball: PTFE
- Seat Material: Stainless steel
- O-Ring Material: PTFE
- Porting: Suction right / discharge right
- Stainless steel hardware
- Plastic muffler

F200-TAE-HB3B-S70

- Connection Type: Tri-Clamp
- Air Section Material: Aluminum
- Diaphragm: Hytrel®
- Ball: Buna-N (FDA)
- Seat Material: Stainless steel
- O-Ring Material: Buna-N (FDA)
- Porting: Suction right / discharge right
- Stainless steel hardware
- Plastic muffler

F200-TAE-4S3M-S70

- Connection Type: Tri-Clamp
- Air Section Material: Aluminum
- Diaphragm: Santoprene® (FDA)
- Ball: Santoprene® (FDA)
- Seat Material: Stainless steel
- O-Ring Material: EPDM (FDA)
- Porting: Suction right / discharge right
- Stainless steel hardware
- Plastic muffler

Materials

Elastomer	Description	Temperature Range	Flex Life	General Use	Strengths	Weaknesses
Buna-N (Nitrile)	A general purpose elastomer used in a variety of industries because of its tensile strength and versatility	10°F to 180°F -12°C to 82°C	Low	Water and Oils	Suitable for Petroleum/ Oily Products High Abrasion Resistance	Low Chemical Resistance
Geolast®	An injection molded thermoplastic material with similar characteristics to Buna-N	10°F to 180°F -12°C to 82°C	High	Water and Oils	Suitable for Petroleum/ Oily Products High Abrasion Resistance	Low Chemical Resistance
Hytrel®	A thermoplastic polyester elastomer that is both strong and flexible	10°F to 180°F -12°C to 82°C	High	Water and Oils	Suitable for Petroleum/ Oily Products High Abrasion Resistance	Low Chemical Resistance
EPDM	A general purpose synthetic rubber that is resistant to a variety of chemicals and has a large temperature range	-40°F to 280°F -40°C to 138°C	Low	Some Acids and Bases	Resistant to Mild Chemicals	Not Suitable for Oily/Petroleum Products
Santoprene®	An Injection molded material with similar characteristics to EPDM	-40°F to 225°F -40°C to 107°C	High	Some Acids and Bases	Resistant to Mild Chemicals and Abrasives	Not Suitable for Oily/Petroleum Products
PTFE	A specialty synthetic thermoplastic that has high chemical compatibility and can withstand caustic liquids	40°F to 220°F 4°C to 104°C	Medium	Most Chemicals	Inert to Most Chemicals	Low Abrasion Resistance
FKM (Viton)	A thermoset rubber elastomer with high chemical resistance and a large temperature range	-40°F to 350°F -40°C to 177°C	Very Low	Wide Variety of Acids and Bases	Large Temperature Range Good Corrosion Resistance Good Chemical Resistance	Low Flex Life

Geolast® is a registered trademark of ExxonMobil Chemical Co.

Santoprene® is a registered trademark of ExxonMobil Chemical Co.


Hytrel® is a registered trademark of DuPont Performance Elastomers L.L.C.



F200 Capacity Curves


MODEL: F200 METAL PTFE

Diaphragm Material: PTFE



MODEL: F200 METAL RUBBER

Diaphragm Material: Santoprene






Capacity Curves


MODEL: F200 METAL TPE


Diaphragm Material: Hytrel



Note:

This diagram displays the standard discharge ports







F200 Parts List

Part #	Part Name	Quantity	Pump Models	Part Number	Material
10.	Discharge Manifold (Tri-Clamp)	1	All Models	10560-75	Stainless Steel
20.	Ball	4	F200-T*E-*B**-* F200-T*E-*S**-* F200-T*E-*T**-*	11009-14 11009-23 11009-45	Buna-N (FDA) Santoprene (FDA) PTFE
30.	Valve Seat	4	F200-T*E-*3**-*	10925-26	Stainless Steel
40.	O-Ring, Valve Seat	4	F200-T*E-*B**-* F200-T*E-*T**-* F200-T*E-*M**-*	11917-14 11917-17 11917-81	Buna-N (FDA) PTFE EPDM (FDA)
50.	Outer Chamber	2	All Models	10725-75	Stainless Steel
60.	Intermediate	1	F200-TAE-*-*-* F200-T3E-*-*-*	11525-20 11525-26	Aluminum Stainless Steel
61.	Inner Chamber	2	F200-TAE-*-*-* F200-T3E-*-*-*	11805-20 11805-26	Aluminum Stainless Steel
70 & 90.	Diaphragm Rod Assembly	1	All Models	35002-00	Stainless Steel
80.	Pilot Valve	1	All Models	10107-31	Acetal
100.	Inner Spacer, Pilot Sleeve	3	All Models	10205-40	Polypropylene
110.	O-Ring (Pilot Sleeve Spacer)	4	All Models	11919-16	Urethane
120.	End Spacer, Pilot Sleeve	2	All Models	10208-40	Polypropylene
130.	O-Ring (End Spacer)	2	All Models	11919-11	Nitrile
140.	Lip Seal (Diaphragm Rod)	2	All Models	12002-76	Nitrile
150.	Retaining Plate	2	All Models	12717-54	Nylon
160.	Bumper	2	All Models	12317-16	Urethane
170.	Inner Diaphragm Plate	2	F200-TAE-*-*-* F200-T3E-*-*-*	11113-20 11113-26	Aluminum Stainless Steel
180.	Diaphragm (Backup)	2	F200-T*E-H***-* F200-T*E-4***-* (B-Up) F200-T*3-T***-*	10611-18 10611-80 10611-80	Hytrel (FDA) Santoprene (FDA) Santoprene (FDA)
190.	Overlay (Diaphragm)	2	ONLY F200-T*3-T***-*	11408-59	PTFE
200. & 210.	Outer Diaphragm Plate w. Threaded Stud	2	F200-T*E-*-*-*	11218-75	Stainless Steel
220.	Suction Manifold (Tri-Clamp)	1	All Models	11338-75	Stainless Steel
230.	Air Valve Gasket	1	All Models	12124-19	Nitrile
240.	Shuttle Plate	1	All Models	10450-77	Ceramic
250.	Shuttle	1	All Models	10430-00	Special
260.	Air Valve Body	1	F200-TAE-*-*-* F200-T3E-*-*-*	11618-20 11618-26	Aluminum Stainless Steel
270.	Air Valve Spool	1	All Models	10483-31	Acetal
280.	Lip Seal (Air Valve)	2	All Models	12003-76	Nitrile
290.	O-Ring (Air Valve End Plug)	1	All Models	11913-11	Nitrile
300.	Air Valve End Plug	1	F200-TAE-*-*-* F200-T3E-*-*-*	11706-20 11706-26	Aluminum Stainless Steel
311. & 312.	Muffler w. Bushing	1	Standard Optional	13013-00 13010-00	Polypropylene Metal
320.	Inner Chamber Gasket	2	All Models	12123-19	Nitrile
340.	Self-Locking Phillips Screw (#6-32 X 3/8")	6	All Models	12571-26	Stainless Steel



F200 Parts List

Part #	Part Name	Quantity	Pump Models	Part Number	Material
351.	Cap Screw (1/4" - 20 X 3")	4	All Models	12516-26	Stainless Steel
352.	Cap Screw (5/16"-18 X 3/4")	10	All Models	12536-26	Stainless Steel
353.	Cap Screw, Flanged (1/2"-13 X 2-1/4")	28	All Models	12572-225-26	Stainless Steel
361.	Nut, Flange (1/2" - 13)	24	All Models	12582-26	Stainless Steel
362.	Nut (5/8" - 11)	2	All Models	12579-25	Plated Steel
381.	Washer, Lock Star (1/4")	4	All Models	12350-26	Stainless Steel
382.	Washer, Flat (1/4")	4	All Models	12300-26	Stainless Steel
383.	Washer, Flat (5/16")	10	All Models	12310-26	Stainless Steel
384.	Washer, Lock Split (1/2")	28	All Models	12323-26	Stainless Steel
385.	Washer, Flat (1/2")	28	All Models	12306-26	Stainless Steel